



Valid For:

**SODIUM SULFATE, ANHYDROUS**  
Deer Park, TX

**CAS No. 7757-82-6**

**Grade:** Glass and Pulp & Paper

**Available in Bulk:** Hopper Car & Hopper Truck

**Rail Carrier:** UP & BNSF

---

**TYPICAL PROPERTIES**

---

**PROPERTIES**

**TYPICAL VALUES**

Sodium Sulfate (Na <sub>2</sub> SO <sub>4</sub> ), %	99.50 min
Loss on Ignition, %	0.50 max
Chloride, ppm	50 max
Iron, ppm	10 max
Sodium Carbonate, %	0.20 max
pH of 5% Aqueous Solution	5 – 7
Water Insolubles, %	0.10 max
APHA Color of 5% Aqueous Solution	15 max
Bulk Density, lbs/ft <sup>3</sup>	85 - 95

**US SCREENS**

**% RETAINED**

20	1.0 max
40	1.0 max
60	3 – 10
80	10 – 20
100	5 – 15
200	40 – 60
Pan	10 - 20

**NOTICE:** Saltex, LLC makes no warranty or representation as to the suitability of the product as specified for any particular application. The determination of the suitability of the above specification for any particular use is solely the responsibility of the user.

All precautionary labels and notices should be read and understood by all supervisory personnel and employees before using. Consult Saltex, LLC and OSHA regulations for additional safety and health information. Purchaser is responsible for complying with all federal, state or local laws and regulations covering use of the product. Special attention should be given to consumer applications. Freedom to use any patent owned by Saltex, LLC or others is not to be inferred from any statement contained herein.